


LT200



► Type LT200

Type key ► page 20



Expansion joint for air conditioning and ventilation systems up to 200°C

Design:	Straight or conical fabric expansion joint made from silicon with a fabric insert and self-sealing flanges or sleeve for clamped fixing Optional single-part backing flanges or fastening clamps
Installation method:	Fixing to flanges or using clamps at duct level
Dimensions:	For round, rectangular and oval duct cross sections
Installation length:	According to customer specification
Media temperature:	Suitable from -60 to +200°C, maximum 250°C
Pressure:	Up to ±15,000 Pa
Movement:	For axial and lateral movements

Application:

Power plants, waste incineration plants, cement factories, paper industry e.g. on ventilators, in air conditioning and ventilation ducts



Flanges

Design:	Single-part backing flange with clearance holes
Flange norms:	According to customer specification
Materials:	Carbon steel: 1.0038 (S235JRG2) Stainless steel: 1.4301 (X5CrNi18-10) 1.4571 (X6CrNiMoTi17-12-2) Other materials on request
Coating:	Primed, hot-dip galvanised, special paint

Fastening clamps

Design:	Depending on pressure and the nominal diameter, endless clamp belt, screw thread belt, small clamps or hinge bolt clamps. At higher pressures, 2 adjacent clamps per fastening side.	
Width:	Endless clamp belt: $\frac{3}{4}$ "	
	Screw thread belt: $\frac{1}{2}$ "	
	Small clamp: depending on \varnothing : 9 – 12 mm	
	Hinge bolt clamp: depending on \varnothing : 18 – 30 mm	
Materials:	Endless clamp belt with screw lugs (tongs):	1.7300
	Screw thread belt with threaded screw lugs:	1.4310
	Small clamp, belt and housing:	1.4016 (Screw steel galvanised)
	Hinge bolt clamp, belt and housing:	1.4016 (Screw steel galvanised)

Flow liners

Design:	Cylindrical, conical or telescoping flow liner (▶ page 298)
Materials:	Carbon steel: 1.0038 (S235JRG2) Stainless steel: 1.4301 (X5CrNi18-10) 1.4571 (X6CrNiMoTi17-12-2) Other materials on request
Coating:	Primed, hot-dip galvanised, special paint

Optional accessories

Fixing:	Screws Nuts Washers Disc springs
----------------	---

Planning help LT200

